



SITE SPECIFIC REQUIREMENTS		
COUNT	DESCRIPTION	INSTALLED BY
	FILTERRA SURFACE AREA (m ²)	OCEAN PROTECT
	MULCH VOLUME (m ³)	OCEAN PROTECT
	FILTERRA MEDIA DEPTH (mm)	OCEAN PROTECT
	VOLUME OF UNDERDRAIN STONE (m ³)	OCEAN PROTECT
	FILTERRA LINER (m)	OCEAN PROTECT

GENERAL NOTES

- OCEAN PROTECT TO PROVIDE ALL MATERIALS UNLESS NOTED OTHERWISE.
- PLANT, MULCH, AND DISSIPATION ROCK ARE SUPPLIED BY OCEAN PROTECT AND DELIVERED AT TIME OF SYSTEM ACTIVATION. PLANT SELECTION SHALL BE DONE BY THE CERTIFYING ENGINEER IN ACCORDANCE WITH THE OCEAN PROTECT PLANT LIST.
- INTERNAL PIPES AND FITTINGS SUPPLIED AND INSTALLED BY OCEAN PROTECT.
- SITE SPECIFIC PRODUCTION DRAWING WILL BE PROVIDED ON PLACEMENT OF ORDER.
- FILTERRA WATER QUALITY STRUCTURE SHALL BE IN ACCORDANCE WITH ALL DESIGN DATA AND INFORMATION CONTAINED IN THIS DRAWING.
- STRUCTURE SHALL BE IN ACCORDANCE WITH AS3600.

INSTALLATION NOTES

- ANY SUB-BASE, BACKFILL DEPTH, AND/OR ANTI-FLOTATION PROVISIONS ARE SITE-SPECIFIC DESIGN CONSIDERATIONS AND SHALL BE SPECIFIED BY CERTIFYING ENGINEER.
- CONTRACTOR TO PROVIDE ALL EQUIPMENT WITH SUFFICIENT LIFTING AND REACH CAPACITY TO LIFT AND SET THE STORMFILTER STRUCTURE (LIFTING DETAIL PROVIDED SEPARATELY).
- CONTRACTOR TO APPLY SEALANT TO ALL JOINTS AND TO PROVIDE, INSTALL AND GROUT INLET AND OUTLET PIPES.
- CONTRACTOR SHALL TAKE APPROPRIATE MEASURES TO PROTECT CONSTRUCTION RELATED SEDIMENT RUN-OFF FROM ENTERING THE FILTERRA MEDIA
- OCEAN PROTECT IS RESPONSIBLE FOR ACTIVATION OF THE SYSTEM AND INSTALLATION OF THE SELECTED PLANT FROM THE OCEAN PROTECT FILTERRA PLANT LIST. ACTIVATION ONLY OCCURS WHEN THE SITE IS FULLY STABILIZED, FINAL PAVEMENT INSTALLED AND SWEEPED CLEAN OF CONSTRUCTION SEDIMENT.

